



Cargo Gear & Capacity Details

Cargo Gear	4 / MacGregor –Haeggglunds / electro-hydraulic
	SWL Outreach
	60 mt 20 m
	50 mt 24 m
	40 mt 30 m

Holds / Hatches

5 Holds

Hold 1 (cbf) / hold 2-3-4 (cbf)	Grain: 117986 / 1158180 Bale: 3294 m ³ / 32295 m ³
Hold 5 (cbf)	Grain: 153054 Bale: 4248 m ³
Dimensions hold 1 (m) (l x b x h)	12.60 x 20.04 / 10.19
Dimensions hold 2-3-4 (m) (l x b x h)	25.60 x 24.40 / 14.85
Dimensions hold 5 (m) (l x b)	12.80 x 24.40
Tons/sq.M tanktop (mt)	Uniform load 20 T/m ²
Tons/sq.M hatch cover (mt)/	4 T/m ²
Hatch dimensions hold no. 1	l x b = 12.60m x 10.19m / 20.04
Hatch dimensions hold no. 2-3-4	l x b = 25.60m x 24.40m
Hatch dimensions hold no. 5	L x b = 12.80m x 24.40m

General Details

Technical Details

Vessel Type	Geared Multipurpose Dry Cargo	Tonnage	
Port of Registry	Monrovia	Hull Type	Double Skin
Flag	Liberia	Dead Weight	33271 Summer/32 255 Winter
Shipyard	Zhejiang Ouhua Shipbuilding Co. Ltd.	Gross Tonnage	22863
Year of Built	2011	Nett Tonnage	10602
Class. Society	DNV	Dimension	
IMO Number	9594482	Length	179.50
Call Sign	D5AD5	Breadth	28.00
Ex-Name	AAL Jupiter	Depth	15.10
		Draft	10.00

Machinery

Main engine	Doosan-MAN B&W 6S50 MC-C7
Power	MCR abt. 8800 kW at 127 RPM
Speed/ Consumption	abt. 14 kn abt. 29.50 mt HFO abt. 13 kn abt. 24.50 mt HFO
Aux Engine	1 Wärtsilä 670W4L20 670 kW at 1000 RPM 2 Wärtsilä 520W4L20 520 kW at 1000 RPM

-all details given in good faith and believed to be true & correct however without guarantee-